



Dual Switch Series-WR229

Specification:

Parameter	Waveguide		Coaxial		
	3.9 to 4.9	DC to 3	3 to 8	8 to 12.4	12.4 to 18
Frequency: (GHz)	3.9 to 4.9	DC to 3	3 to 8	8 to 12.4	12.4 to 18
VSWR: (Max.)	1.05	1.2	1.3	1.4	1.5
Insertion Loss: (Max.)	0.02dB	0.02dB	0.03dB	0.04dB	0.05dB
Isolation: (Min.)	80dB	80dB	70dB	60dB	60dB

Flange:	optional
Voltage:	optional
Switching Time:	200 mS Max
Pressure	30 PSIG (RF Head Only)
Drive	Motor
Operating Temp	-40 °C to +85 °C
Non- Operating Temp	--55 °C to +100 °C
Humidity:	0 to 100%, Fully Weatherized

Options:

CIRCUIT OPTIONS
NO INDICATORS
1 SET INDICATORS
2 SETS INDICATORS
3 SETS INDICATORS
4 SETS INDICATORS
INHIBIT CIRCUITS

VOLTAGE OPTIONS
12 VDC
15 VDC
24 VDC
28 VDC
48 VDC
115 VAC
230 VAC

DRIVE OPTIONS
LATCHING
PULSE
FAILSAFE
TTL

FLANGE OPTIONS
COVER
GROOVE